

## Venue

### Specifications

Product definition	: tufted loop pile
Gauge	: 1/10"
No. of tufts	: 148400/m <sup>2</sup>
Pile fibre	: 100% PA SDN
Pile weight	: 600 gr/m <sup>2</sup> ± 5%
Pile height	: 2.9 mm ± 5%
Primary backing	: PA/PES non-woven - Colback
Tile backing	: Polyflex with a non-woven fabric
Total thickness	: 6 mm ± 7.5%
Total weight	: 4350 gr/m <sup>2</sup> ± 7.5%
Tile size	: 50x50 cm (± 19.7"x19.7")
Tiles per box	: 20

### Performance

Use classification		: Class 33
Castor chair test	EN 985	: A, continuous use
Abrasion	EN 1963	: pass
Vettermantest	ISO TR 10361/ EN 1471	: pass
Thermal isolation	ISO 8302	: 0.09m <sup>2</sup> K/W
Dimensional stability	ISO 2551	: pass

### Electrostatic Properties

Walk on test	ISO 6356	: -0.1 Kv
Horizontal electrical resistance	ISO CD 10965	: 8x10 <sup>9</sup> Ω
Vertical electrical resistance	ISO CD 10965	: 4x10 <sup>9</sup> Ω
Static loading		: anti-static

### Flame properties

Reaction to fire	EN ISO 11925-2 EN ISO 9239-1	: Bfl - s1
Hot metal nut test	BS 4790	: Low Radius

### Colour fastness properties

Light	ISO 105 B02	: > 5.0
Rubbing, dry	ISO 105 X12	: 4.5
Rubbing, wet	ISO 105 X12	: 5.0
Shampoo	BS 1006	: 4.5
Water	ISO 105 E01	: 5.0
Water stains	TNO W 6024	: 5.0